

SPECIFICATIONS

MODEL	Tanglewood T6 Acoustic Amplifier
POWER OUTPUT (RMS)	60W
SPEAKER/IMPEDANCE	8"/4 ohm
IMPEDANCE INPUT	CH1: 470K Ω
	CH2: LINE- 22K Ω /MIC-600 Ω
BUILT-IN EFFECTS	HALL, PLATE, CHORUS, DELAY
INPUT JACK(6.35mm)	CH1 INPUT, CH2 INPUT(6.35mm+XLR)
	AUX IN(RCA), MP3 IN(3.5mm)
	TURNER OUT, SEND/RETURN, DI OUT(XLR)
	LINE OUT, PHONES OUT, FOOTSWITCH
INDICATOR	POWER LED, INDICATOR FOR CH1/CH2 OVERDRIVE.
POWER SUPPLY	AC 100V/50Hz-60Hz, 110V/60Hz, 220V/50Hz, 230V/50Hz, 240V/50Hz
NET WEIGHT	11.0Kg
GROSS WEIGHT	12.5Kg
DIMENSIONS	346x280x346mm
PACKING SIZE	430x370x420mm
ACCESSORIES	Owner's Manual, Power Cord. T6 Gig Bag available separately
SPEAKER SOCKET	35mm Recessed Speaker Pole Socket